



Multi-Horsepower Replacement Motors from Emerson



Think of them as service call insurance.

Now you'll always have a motor when you need it.

The Rescue® motors replace a variety of different horsepower applications.

RESCUE will eliminate the need for temporary substitutions, extra driving time to get the right motor, or emergency openings in the evening.

You may not know what kind of motor you will need, but with the RESCUE motors on hand, you know you'll have one that will work.

Furnace Motors

5460 Replaces 115V 1/2 to 1/6 HP

5461 Replaces 208-230V 1/2 to 1/6 HP

- 48 Frame, 5.6 Inch Diameter
- 1075 RPM applications
- Mounts with Thru-Bolts, Shell Holes or Belly Band
- 36 Inch Leads
- Extended Mounting Studs
- 2.5" Diameter Hub Rings Included
- Reversible Rotation
- All-Position Mount

5470 Replaces 115V 3/4 to 1/5 HP

5471 Replaces 208-230V 3/4 to 1/5 HP

- Same as **5460** and **5461** but Features 3/4 HP and Ball-Bearing Design

Condenser Fan Motors

5464 Replaces 825 RPM 1/3 to 1/6 HP

5462 Replaces 1075 RPM 1/3 to 1/6 HP

5465 Replaces 1075 RPM 1/2 to 1/5 HP

- 48 Frame, 5.6 Inch Diameter
- 208-230V
- 140°F (60°C) Ambient Rated
- Special Treated Rotor for Longer Life
- Mounts with Thru-Bolts, Lead End and Side Shell Holes or Belly Band
- 48 Inch Leads with Flag Terminals
- Extended Mounting Studs
- Ball-Bearing Design
- Reversible Rotation
- All-Position Mount Totally Enclosed
- Flat Lead End for Shaft Down Applications

Direct Drive Fan & Blower Motors

3/4 HP



**5470 (115V)
5471 (208-230V)**

Features: Extended Mounting Studs, Resilient Rings, Rheem Mounting Holes, Ball Bearings, Reversible
Wt. 22 lbs.

MOTOR TO REPLACE	SPEEDS TO USE* (COLOR/APPROX. RPM)		370V CAPACITOR	5470 115V FLA	5471 208-230V FLA
	COOLING	HEATING			
3/4 HP	High (Black/1110)	Med-Hi (Blue/1080) or Med-Low (Yellow/1010)	20 mfd	8.1	3.8
1/2 HP	High (Black/1130)	Med-Low (Yellow/1090) or Low (Red/1035)	10 mfd	6.6	3.7
1/3 HP	Med-Hi (Blue/1150)	Med-Low (Yellow/1130) or Low (Red/1100)	10 mfd	4.6	2.5
1/4 HP	Med-Low (Yellow/1150)	Low (Red/1130)	10 mfd	3.8	1.8
1/5 HP	Low (Red/1140)	Low (Red/1140)	10 mfd	3.1	1.7

1/2 HP



**5460 (115V)
5461 (208-230V)**

Features: Extended Mounting Studs, Resilient Rings, Reversible, Rheem Mounting Holes
Wt. 15 lbs.

MOTOR TO REPLACE	SPEEDS TO USE* (COLOR/APPROX. RPM)		370V CAPACITOR	5460 115V FLA	5461 208-230V FLA
	COOLING	HEATING			
1/2 HP	High (Black/1100)	Med-Hi (Blue/1050) or Med-Low (Yellow/825)	10 mfd	7.3	3.6
1/3 HP	High (Black/1120)	Med-Hi (Blue/1090) or Med-Low (Yellow/1030)	5 mfd**	6.9	3.5
1/4 HP	Med-Hi (Blue/1125)	Med-Low (Yellow/1090) or Low (Red/1010)	5 mfd**	5.5	2.8
1/5 HP	Med-Low (Yellow/1110)	Low (Red/1060)	5 mfd**	3.6	1.9
1/6 HP	Low (Red/1085)	Low (Red/1085)	5 mfd**	2.8	1.3

** Using a 7.5 mfd/370V capacitor will result in an approximately 10% stronger motor. This can be used where there is more air flow needed.

Condenser Fan Motors



Features: 48 Frame, 5.6" Diameter, 48" Leads, 140°F (60°C) Ambient Rated, All Position Mounting, Ball Bearings, Totally Enclosed (air over), Reversible, Lead End & Rheem Side Shell Mounting Holes

5464 (208-230V)

825 RPM applications
Wt. 18 lbs.

5462 (208-230V)

1075 RPM applications
Wt. 14 lbs.

5465 (208-230V)

1075 RPM applications
Wt. 19 lbs.

MOTOR TO REPLACE	SPEED TO USE (COLOR/RPM)*	CAP. MFD***			MOTOR TO REPLACE	SPEED TO USE (COLOR/RPM)*	CAP. MFD***			MOTOR TO REPLACE	SPEED TO USE (COLOR/RPM)*	CAP. MFD***		
		208V	230V	FLA			208V	230V	FLA			208V	230V	FLA
1/3 HP	High (Black/825)	10	7.5	1.9	1/3 HP	High (Black/1110)	7.5	5	2.6	1/2 HP	High (Black/1110)	12.5	10	3.0
1/4 HP	High (Black/835)	10	7.5	1.5	1/4 HP	High (Black/1135)	7.5	5	2.5	1/3 HP	High (Black/1135)	12.5	10	2.2
1/5 HP	Low (Red/825)	10	7.5	1.2	1/5 HP	Low (Red/1110)	7.5	5	2.0	1/4 HP	Low (Red/1110)	12.5	10	1.6
1/6 HP	Low (Red/835)	10	7.5	1.0	1/6 HP	Low (Red/1125)	7.5	5	1.8	1/5 HP	Low (Red/1125)	12.5	10	1.3

* RPM data from cold motor at nominal horsepower. Actual load will determine effective rpm.



2002-EM-99 R3 (12/06) Emerson™, Emerson. Consider It Solved™, Emerson Climate Technologies™ and the Emerson Climate Technologies™ logo are the trademarks and service marks of Emerson Electric Co. and are used with the permission of Emerson Electric Co. Rescue® is a trademark and service mark of Emerson Motors. All other trademarks are the property of their respective owners. © 2006 Emerson Climate Technologies, Inc. All rights reserved. Printed in the USA.



EMERSON
Climate Technologies

EMERSON. CONSIDER IT SOLVED.™